

**SS241B系列高温高压纱线染色机**  
 SS241B Series HTHP Yarn Dyeing Machine

**技术数据**

- ◇ 浴比: 1: 5
- ◇ 设计温度: 160°C
- ◇ 最高工作温度: 140°C
- ◇ 设计压力: 0.5Mpa
- ◇ 最高工作压力: 0.45Mpa
- ◇ 加热率: 20°C~130°C约30分钟(蒸汽压力为0.7Mpa)
- ◇ 冷却率: 130°C~80°C约20分钟(冷却水压力为0.3Mpa)

**Technical Data**

- ◇ Liquor ratio:1:5
- ◇ Design temperature: 160°C
- ◇ Maximum working temperature: 140°C
- ◇ Design pressure: 0.5Mpa
- ◇ Max working pressure: 0.45Mpa
- ◇ Heating rate: 20°C~130°C in about 30 minutes(steam pressure 0.7Mpa)
- ◇ Cooling rate: 130°C~80°C in about 20 minutes(cooling water pressure 0.3Mpa)

**规格表 Specification**

型号(Model)	载重Capacity(kg)			起吊高度H Lifting Height H mm
	纱杆数量 No.of Spindles	每杆筒子纱数量 No.of Packages Per Spindle	载重 Capacity(kg)	
SS241B-1-8	1	1-8	1-8	
SS241B-10	4	3	12	2810
SS241B-15	4	4	16	3148
SS241B-25	6	5	30	3590
SS241B-50	9	6	54	4275
SS241B-100	19	6	114	4290
SS241B-150	19	8	152	4980
SS241B-200	30	9	270	5875
SS241B-300	36	9	324	5950
SS241B-350	46	9	414	6110
SS241B-350H	46	11	506	6715
SS241B-550	69	9	621	6160
SS241B-550H	69	12	828	7098
SS241B-1200	108	9	972	6710
SS241B-1200H	108	12	1296	7790
SS241B-2000	108	16	1728	9325
SS241B-2500	204	11	2244	9910
SS241B-2250	132	14	1848	8575
	132	15	1980	8850
	132	16	2112	9130
	132	17	2244	9530
	132	18	2376	9875
	132	19	2508	10168
	132+126	10(只/double)	2580	9180
	132+122	12(只/double)	3048	10285

**SS241N系列高温高压纱线染色机**  
 SS241N Series HTHP Yarn Dyeing Machine

**技术数据**

- ◇ 浴比: 1: 5
- ◇ 设计温度: 160°C
- ◇ 最高工作温度: 140°C
- ◇ 设计压力: 0.5Mpa
- ◇ 最高工作压力: 0.45Mpa
- ◇ 加热率: 20°C~130°C约30分钟(蒸汽压力为0.7Mpa)
- ◇ 冷却率: 130°C~80°C约20分钟(冷却水压力为0.3Mpa)

**Technical Data**

- ◇ Liquor ratio:1:5
- ◇ Design temperature: 160°C
- ◇ Maximum working temperature: 140°C
- ◇ Design pressure: 0.5Mpa
- ◇ Max working pressure: 0.45Mpa
- ◇ Heating rate: 20°C~130°C in about 30 minutes(steam pressure 0.7Mpa)
- ◇ Cooling rate: 130°C~80°C in about 20 minutes(cooling water pressure 0.3Mpa)

**规格表 Specification**

型号 (Model)	载重Capacity(kg)			起吊高度H Lifting Height H mm
	纱杆数量 No.of Spindles	每杆筒子纱数量 No.of Packages per Spindle	载重 Capacity(kg)	
SS241N-21	1	1-8	1-8	
SS241N-42	4	10	40	4860
SS241N-50	5	10	50	4980
SS241N-55	6	10	60	5025
SS241N-70	9	12	108	5872
SS241N-75	12	12	144	5895
SS241N-90	19	12	228	6100
SS241N-95	20	12	240	6156
SS241N-110	30	12	360	6490
SS241N-115	32	12	384	6635
SS241N-120	36	12	432	6670
SS241N-130	41	12	492	6715
SS241N-140	46	12	552	6818
SS241N-152	57	12	684	7020
SS241N-170	69	12	828	7100
SS241N-187	91	12	1092	7219
SS241N-200	108	12	1296	7140
SS241N-225	132	16	2112	8746